

High-Performance LCD Expansion Module

The EXP40 Expansion Module for the SIP-T46G, expanding the functional capability of your sip phone to a whole new level. It features a large graphic LCD. Two pages of 20 flexible buttons are shown on the display can be programmed up to 40 various features, the productivity-enhancing features include BLF/BLA, speed dialing, call forward, transfer, park, pickup, etc.



Key Features and Benefits

Revolutionarily new design

New design pursuing tiniest details for matching elegantly with the look and feel of T46G, rubber covers on the feet that contact the desk surface help prevent the phone from sliding, The new foot stand allows two positions for the device, support application of wall mountable, the backlit display eliminates the need for external light.

A rich visual experience for applications

Equipped with a 160x320 graphic LCD with Backlight. 20 physical keys each with a dual-color LED and two page views are possible, this allows 40 additional programmable keys that can be used for speed dialing, BLF/BLA, call forward, transfer, park, pickup, etc. 2 independent control keys are used for fast switch pages.

Expandability

The PSU version supports up to 6 Expansion Module, adding up to 240 additional buttons. The PoE version supports 2 EXP-40 Expansion Module, adding up to 80 additional buttons. it can also be powered by a conventional power supply (5V/1.2A) if you need.

- > An exclusive collection which quality and detailed designs
- > Rich visual experience with 160x320 graphic LCD
- > 20 physical keys each with a dual-color LED
- > 2 independent control keys are used for fast switch pages
- > Stand with 2 adjustable angles
- > Wall mountable

Display

- > 160x320 graphic LCD with 16-level greyscales
- > LCD Backlight
- > Two page views are possible
- > Different icons for each function shown on the LCD

Features Keys and Indicator

- > 20 physical keys each with a dual-color LED
- > 20 additional keys through page switch
- > 2 independent control keys are used for fast switch pages
- > Programmable for Shared Line, BLF List, BroadSoft Group, Call Park, Conference, Forward, Group pickup Group listening, LDAP, Pick UP, XML Browser, Zero-SP-Touch.....

Package Features

- > Qty/CTN:
- > N.W/CTN:
- > G.W/CTN:
- > Measurement:
- > Carton Meas:

Physical Feature

- > Wall mountable
- > Stand with 2 adjustable angles
- > The PSU version supports up to 6 EXP-40, The PoE version supports up to 2 EXP-40
- > 2xRJ12 (6P6C) ports for data in and out
- > Power adapter: AC 100~240V input and DC 5V/1.2A output
- > Dimension (W*D*H*T): 127MM*213MM*167MM*45MM
- > Applies to Yealink IP Phone
- > Operating temperature: -10~50°C
- > Operating humidity: 10-95%



SIP-T46G+EXP40

Learn More

To find out how Yealink solutions can help your organization, visit us at www.yealink.com or mail to sales@yealink.com

Addr: 4th-5th Floor, South Building, No.63 Wanghai Road, 2nd Software Park, Xiamen, China

Web: www.yealink.com

Tel: +86-592-5702000

Email: sales@yealink.com